

FibreGrid GRP Threshold Access Ramp



Product Description

Our GRP Threshold Access Ramps are important to provide provision for those with mobility disabilities. GRP Threshold Access Ramps are engineered to exceed current DDA legislation and is manufactured to ISO 9001 standards so you can be sure they are of the highest quality.

The fibreglass and aluminium ramps are essential for overcoming physical barriers at your premises for disabled persons. Access ramps are the most economical solution for dealing with these barriers.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733





Characteristics

- High load capacity - our high quality fibreglass and aluminium access ramps can withstand a load capacity of 250kg.
- Lightweight
- Anti slip - the heavy duty GRP fibreglass surface makes our ramps ideal for providing an anti slip surface to a variety of vehicle and foot traffic.
- DDA compliant and manufactured to meet ISO 9001 standards.



Suitable Substrates & Applications

- Private building access
- Commercial building access
- Fire escapes
- Interior steps
- Exterior steps
- Wood
- Concrete
- Stone
- Metal



Technical Data

GRP Threshold Access Ramp					
Size	Height	Length	Internal Width	Overall Width	Weight
Small	75mm	450mm	760mm	760mm	3.5kg
Medium	100mm	450mm	760mm	760mm	4kg
Large	125mm	450mm	760mm	760mm	4.25kg

Load capabilities:	250kg
Design life:	20+ years (subject to traffic analysis)
General use:	Standard pedestrian, wheelchair/mobility scooter traffic

Meets DDA Regulations: The Disability Discrimination Act states that service providers have to make “reasonable adjustments” in relation to the physical features of their premises to overcome physical barriers to access. Our GRP Threshold Access Ramps meet these requirements.

Slip Resistant Surface: Our GRP Threshold Access Ramps incorporate our standard grit top surface providing an excellent slip resistant surface even in extreme weather conditions. An important factor given ramps are generally used externally.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



001



High Quality Materials: If you are choosing either the fibreglass or aluminium ramps you can be assured that both sets of ramps are made to an extremely high specification ensuring the product's long life even in external applications.

High Load Capacity: With the increasing number of motorised access vehicles on the market, sometimes weighing up to 100kg, the high quality construction means that the ramps are able to cope with loads of up to 250kg.

Application

Unpack the ramp and simply butt up to the step, ensuring the ramp is level with the step height.

Ensure that the substrate is level and the ramp sits evenly.

The table below is for guidance purposes only and assumes assisted access on a gradient of 1:6.

Step height	Suitable ramp (step height should be exact size)
75mm (3 inches approx.)	75mm Threshold Ramp
100mm (4 inches approx.)	100mm Threshold Ramp
125mm (5 inches approx.)	125mm Threshold Ramp

Cleaning

Dirt and debris can easily be removed using a stiff brush and should be carried out on a regular basis. If the ramp has been subjected to spillages or the dirt has become embedded, detergents such as SlipGrip® Degreaser or similar can be used. It is always advisable to test any cleaning product on the Access Ramps before starting the cleaning procedure. This can be done in an inconspicuous area of the product.

Using the detergent, warm water and a suitable brush, scrub the areas until clean. The excess water can be removed using a wet/dry vacuum cleaner or suitable absorbable materials. Where circumstances allow, GRP Threshold Access Ramps can be power washed without causing harm.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



001

