

## FibreGrid SlipGrip® Anti Slip Tape



### Product Description

SlipGrip® Anti Slip Tape is a quick and easy way to alert people to hazards, highlight evacuation routes or to cordon off dangerous areas in your premises.

If you are applying to an environment exposed to water, use SlipGrip® Anti Slip Tape Sealer to waterproof your tape, and to stop water affecting the tape's performance.

For internal and external use (for best results, or if you are applying externally, or on a dusty/porous surface, we recommend you use our SlipGrip® Anti Slip Tape Primer for extra adhesion).

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP  
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: [www.fibregrid.com](http://www.fibregrid.com)  
Email: [sales@fibregrid.com](mailto:sales@fibregrid.com)  
Phone: 01440 712722  
Fax: 01440 712733



001



## Characteristics

- Quick and affordable alternative to GRP
- Self adhesive backing
- Can be used internally or externally
- Water resistant and pressure sensitive
- Disability Discrimination Act and Building Regulations approved
- Long lasting due to the strong resin bonded aluminium grit



## Suitable Applications

- Walkways
- Ramps
- Stairs
- Concrete
- Wood
- Metal
- Stone



## Technical Data

Roll length:	18 metres
Roll width:	50mm 150mm
Colours:	Black Yellow Hazard (Black & Yellow striped)



## Preparation

Ensure the surface is clean, dry, and free from wax, oil, food residue or any other substance likely to affect the application of the tape. Grease and oil should be removed with our SlipGrip® Standard Degreaser.

For best results, use our SlipGrip® Anti Slip Tape Primer for extra adhesion.



## Application

Roll out your anti slip tape to desired length, then cut with a sharp pair of scissors.

If you are using on steps and nosings, leave a gap of about 10mm from the step edge to avoid the tape getting scuffed and thus reducing its life and efficiency.

Peel off the backing strip to a length of approximately 50mm, which gives you more control than if you peel off too much. Then, firm the product into place with a hand or foot.

Do take care not to stretch the tape and only use at temperatures above 10°C.

**Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP**  
**Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA**

**Online:** [www.fibregrid.com](http://www.fibregrid.com)  
**Email:** [sales@fibregrid.com](mailto:sales@fibregrid.com)  
**Phone:** 01440 712722  
**Fax:** 01440 712733



001





# FIBREGRID

If you find you've made a mistake, don't worry as the products can be peeled off easily immediately after fitting, but do this straight away.

If you are fitting on surfaces that could get wet, or are likely to experience heavy traffic, then we recommend you use our Anti Slip Tape Edge Sealer.

Anti Slip Tape should be fitted as per the instructions provided.

### Anti Slip Tape Primer

This is ideal for porous or dusty surfaces. Simply stir and brush on. Coverage is 2-3m<sup>2</sup> per 500ml. The appearance when applied is milky, but it dries (in about one hour at 10-15°C) clear.

Make sure you only apply the primer to areas that the products will cover, otherwise dust could settle on exposed primer.

After application, brushes can be washed out in water.

### Anti Slip Tape Sealer

If you are using the products where moisture could penetrate the tape edge, or in very heavily-trafficked areas, then we recommend you apply our Anti Slip Tape Sealer. All you need to do is squeeze the sealer from the tube around the tape edge. This will give extra protection and increase the tape's life.



## General Maintenance

### Downtime

Although these products can be walked on immediately, full adhesion takes 24 hours, so be gentle with them during this period and avoid heavy use.

### Storage

Keep the product warm and dry before using.

**Southern Office:** Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP  
**Northern Office:** Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

**Online:** [www.fibregrid.com](http://www.fibregrid.com)  
**Email:** [sales@fibregrid.com](mailto:sales@fibregrid.com)  
**Phone:** 01440 712722  
**Fax:** 01440 712733



001



# FIBREGRID