

FibreGrid SlipGrip® Anti Slip Self Adhesive PVC Sheet 1000x1000mm



Product Description

Our SlipGrip Anti Slip Self Adhesive PVC Sheets are a quick and easy solution to slippery floors. Just peel back the self-adhesive and push down in place.

Dimensions: 1000mm width x 1000mm length

A heavy layer of pressure sensitive, water-resistant adhesive bonds the PVC backing to all smooth, non-porous surfaces.

You may need to prepare the substrate with SlipGrip Safety Tape Primer available from our website or call us on 01440 712722.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



Characteristics

- Low profile - no trip hazard
- PVC backed, self adhesive application
- Water resistant pressure sensitive adhesive backing
- Extremely flexible - can be folded at 90° without cracking

Suitable Applications

- Areas with low to medium foot traffic
- Can be used as a temporary or semi-permanent solution to a slippery area

Suitable Substrates

- Wood
- Concrete
- Stone
- Metal

Preparation

Ensure the surface is clean, dry, and free from wax, oil, food residue or any other substance likely to affect the application of the adhesive. Grease and oil should be removed with our SlipGrip Standard Degreaser.

Priming - If your surface is non-porous and dust free, priming isn't necessary. However dusty porous surfaces should be primed with our Anti Slip Tape Primer.

The lower the temperature, the weaker the adhesion, so don't use on temperatures below 10°C. You can cut the sheets with a pair of sharp scissors, so it is easy to get the shape you need.

Application

Peel off the backing strip to a length of approximately 5 - 10cm, which gives you more control when laying the floor in place. Then, firm the product into place with a hand or foot.

If you find you've made a mistake, don't worry as this can be peeled off easily immediately after fitting, but do this straight away.

Continue to peel back the adhesive backing as you push the flooring into place. If you are fitting on surfaces that could get wet, or are likely to experience heavy traffic, then we recommend you use our Anti Slip Tape Edge Sealer.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



Application

Downtime

Although these products can be walked on immediately, full adhesion takes 24 hours, so please take care with them during this period and avoid heavy use.

Storage

Keep the product warm and dry before using.

Slip Resistance Values

Measured using the Pendulum test method (WF rubber slider)
- certificate available on request.

Top Surface	Dry Reading	Wet Reading
Standard	103	66

The UK Slip Resistance Group guide to slip resistance
of a floor for able bodied pedestrians:

Four S Pendulum Value	Potential for Slip
Above 65	Extremely Low
35 to 65	Low
25 to 35	Moderate
25 and Below	High

To ensure that the above slip resistance levels are maintained, the floor sheets should be kept clean.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733

