

## WP70 Oxmine Silicone Sealer



### Product Description

Our WP70 Oxmine Silicone Sealer is a high quality, neutral cure silicone for perimeter sealing of internal and external door and window frames. Rapid curing with good adhesion properties and higher gloss finish.



### Product Characteristics

- Permanently elastic
- Weatherproof
- Non fading
- Suitable for alkaline and metal surfaces
- Low odour and safe to use
- Contains additional uPVC adhesion promoters.



### Suitable Applications

Sealing of wood, aluminium and PVCu door and window frames and for weather sealing and flexible jointing of infill panels.



### Suitable Substrates

Wood, aluminium and PVCu.

# WP70 Oximine Silicone Sealer



## Technical Data

Tooling Time:	5-10 minutes
Tack Free Time:	approx. 30 min at 23°C
Cure rate:	approx. 1mm per day
Shore A Hardness:	approx 20-28
Application temperature:	+5°C up to +45°C
Service temperature:	-60°C up to +160°C
Storage:	Store in shaded dry conditions at room temperature
Shelf life:	12 months if unopened



## Preparation

- Ensure all surfaces are clean, dry and dust and grease-free.
- Porous materials should be primed for optimum adhesion.
- When sealing deep joints use foam backer rods to minimise wastage



## Application

All surfaces must be clean, dry and dust and grease-free. Porous materials should be primed for optimum adhesion. When sealing deep joints use foam backer rods to minimise wastage. Cut the tip of the cartridge, screw on nozzle and cut at an angle of 45°. Apply at temperatures between +5°C and +45°C using a standard sealant gun. Tool the sealant using the appropriate shaped tooling aid - Do not use a wetted finger

Note: risk of yellowing in low UV light situations.

### Limitations

Not suitable for use with aquaria. Not suitable for use on bitumen or asphalt. Over-painting is not recommended. Substrates like marble, sandstone and similarly porous surfaces can show a discolouration around the sealant edges. Not suitable for bedding double glazed windows.



## General Information

### Maintenance

Resistant to all common household cleaning chemicals. In showers and bathrooms best results are obtained with a weekly clean to prevent organic build up.

Stains can be removed with commercial bleach.

Provide regular and sufficient ventilation in closed rooms.

### Please Note

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

Contains 2-Butanone Oxime. Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use.

Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP

Online: [www.fibregrid.com](http://www.fibregrid.com)

Email: [sales@fibregrid.com](mailto:sales@fibregrid.com)

Phone: 01440 712722

Fax: 01440 712733

